



AIRFED GRINDING SYSTEM SUPPLIED AIR



C € ĽK



Navitek® Grinding Visor

KEY FEATURES

- Lightweight shell and longitudinal adjustment headgear
- Large viewing area
- Conforms to EN175B & EN166B
- Weight: 328g
- 1 Year Warranty

Weltek® Airkube Supplied Air Regulator

KEY FEATURES

- Supplied air regulator
- Adjustable airflow
- Sound alarm for low pressure
- Padded belt
- Liaison hose with FR protection
- To be connected to breathable supplied air according to EN 12021
- For confined environments
- Low maintenance
- Quick installation
- Simple use
- 1 Year Warranty

LED Control Panel



TH3 Inward Leakage Classification

Assigned Protection Factor 40 Points



TECHNICAL SPECIFICATIONS

Inlet Pressure	3 - 8 Bar
Adjustable Airflow	170 l/m to 280l/m
Low Airflow Alarm	Yes- Sound Alarm
Inlet Connections	Compatible with Rectus 25, 26,
	CEJN320 & PCL XF
Noise Level	71dB(A)
Weight	635g (with belt)
Certification	EN 14594
Class	3A

ACCESSORIES

Order Code	Description	Pack Qty
AX3415	Clear Lens for Navitek Grinding Visor	. 1.
AX1140	Sweatband	. 1 .
CR7010	Airkos Hose	1
CR7012	Airkos Hose Cover	1
CR7025	Headgear	1
CR7032	Face Seal	1
CR7002	Airkos Harness	1
CR7090	Weltek Red/Black Storage Bag	1 1
AC9001	Airkube Belt	° 1°
AC9009	Airkube Regulator Unit - No Belt or Hose	° 1°
AC9050	Airkube Silencer	° 1°
AC9051	O Ring for Airkube Silencer	° 1°

System Order Code: **AC7700**