ZADICHELMET





tek

Radikally DIFFERENT

Weltek has been a major player in active welding protection since 2003, through continuous innovation, providing effective solutions tailored to the needs of welders.

The innovations of the new Radikal helmet are complemented by developments in our Airkos assisted ventilation system to create the perfect combination.

Optimal comfort, cutting-edge technology, ease of adjustment and perfect balance, the new Radikal helmet offers you the best in respiratory protection.

> SCAN ME FOR MORE INFORMATION



+ 160° viewing area

SIDE VISION IN DIN 5 POLYCARBONATE

160°

FLIP-UP WITH AUTODARKENING FILTER

Badika





SIDE TRIGGER FOR FLIP RELEASE

+ Ease of use

+ Rapid

CLEAR VISOR

+ High level of resistance

ERGONOMIC SHELL & PROFILE

+ Comfort

COMFORT

SIDE AIR

- + Cervical comfort
- + BALANCE + Lightweight
- Lightwoight

QUICK FASTENNING & CHANGE OF FR FACE SEAL, WITHOUT SCREWS

+ Practical & hermetic

UPPER AIR DIFFUSER FACING CLEAR VISOR

+ Limits fogging

LOWER AIR DIFFUSER FACING AIRWAYS


+ Improved breathability with more diffused air

WIDE SWEATBAND


+ Sweat removal without build-up

QUICK RELEASE

+ Longitudinal adjustment







OUTER PROTECTION IN INJECTED POLYCARBONATE

- + High resistance to impacts & scratches
- + Simple rapid replacement of polycarbonate from the outside

AUTODARKENING FILTER

+ TRUE COLORS technology



AUTOSHADE SENSORS

+ Automatic shade adjustment for intensity-dependent welding



DELAY setting, return time 1 SENS setting, sensor sensitivity 2 SHADE setting

Light shade	DIN 3
Number of arc sensors	4 - independent
Switching speed	0.1ms
Viewing area	100x70mm
Welding shades	DIN 5 to DIN 13
Auto-Shade mode	Yes - Can be deactivated
Liquid crystal technology	True Colors
Sensitivity setting	5 levels
Delay setting	5 levels
Optical classes	1/1/1/1
160° side vision	DIN 5 polycarbonate
Power supply	Solar + CR2450 battery
Buttons	Push-loop
Display	LED
Applications	Arc, MIG/MAG, TIG, MicroTig, Pulsed, Cutting
Standards	EN 379, ISO 16321
Warranty	3 years





+ Enhanced safety

TH3 INWARD LEAKAGE

+ 99.8%

Filtration	PRSL
Inward leakage	TH3 (99.8%)
Air flow rate	180 - 220l/m
Digital display	Filter clogging level, Battery charge level, Selected air flow rate
Audible alarm no.1	Filter clogging
Audible alarm no.2	Low battery charge
Battery	Lithium - ion 7.4V / 5200mA, Option HD battery 7.4V / 7400mA
Operating time (with 180l/m air flow rate)	10h - Standard battery, 15h - HD battery
Belt	Large - neoprene, Leather strap option, Harness option
Connecting hose	85cm - With FR cover
Storage/carry bag	Premium bag included
Weight	1180g (unit+battery)
Warranty	1 year (motor and battery)
Standards	EN 12941
Low Voltage Directive	LVD 2006/95/EC




ROLL


Airkos

- 4 Lithium-ion battery charge level
 5 PRSL filter clogging level
- 6 Selected air flow rate

RADIKAL



SPARE PARTS





Intertek

LONDON: 2 Barking Industrial Park | Alfreds Way | Barking | IG11 OTJ T: 020 8591 5777 E: london@wesweld.co.uk KENT: Unit 13b Maritime Close | Rochester | ME2 4DJ T: 01634 296442 E: kent@wesweld.co.uk ESSEX: 19 Crittall Road, Witham CM8 3DR T: 01376 315940 E: essex@wesweld.co.uk