

Includes
TIG torch & adaptor,
gas regulator,
work return lead
& clamp



Combining striking style,
simple operation,
dual voltage versatility
and highly advanced electronics

- High quality tactile rubber finish to mouldings & handle


Key Features

- IGBT Inverter technology - for the professional user
- Dual input voltage
- DC TIG/MMA
- Hot start, HF arc ignition, 2T/4T
- Down slope & post flow
- High frequency inverter, high efficiency
- Compact size, lightweight and modern design
- Heavy duty 35-50mm dinse sockets
- Easy start, stable and reliable arc
- Auto-compensation for voltage fluctuation
- Advanced single PCB construction
- Generator friendly**

Technical Data

	AC 115V/230V - 50/60 Hz	
	115V	230V
Input Voltage		
I _{eff} (A)	18.5	14.2
Input Power (kVA)	4	7
Current Range (A)	TIG 10 - 120 MMA 10 - 100	TIG 10 - 180 MMA 10 - 160
Duty Cycle @ 40°C	120A @ 35%	180A @ 40%
No-Load Voltage (V)	65	
Efficiency (%)	85	
Power Factor	0.7	
Protection/Insulation Class	IP21/F	
Dimensions (LxWxH mm)	365 x 135 x 277	
Weight (Kg)	5.94	

*5 year warranty subject to product registration **Generators should have regulated output



Optional

Trolley

Order Code:
JIT-01

MMA Leads

Order Code:
WCS25-3WEL

Site Bag

Order Code:
JSB-01

Shoulder Strap

Order Code:
JSS-01



The power in inverter technology

Innovative welding technology